

Specifications

| General | |
|---------------------------------|----------------------------------|
| Frequency Range | UHF:400~470MHz |
| Channel Capacity | 16 |
| Channel Spacing | 25KHz/12.5KHz |
| Operating Temperature | -20℃ ~+60℃ |
| Antenna Impedance | 50Ω |
| Operating Voltage | DC 7.4V(±20%) |
| Battery Capacity | 2000mAh(Li-ion) |
| Frequency Stability | ≤±2.5ppm |
| Dimensions | 61(L)×37(W)×132(H)mm |
| Weight | 242g (including battery pack) |
| Transmitter | |
| Power Output | H: 7W L: 1W |
| Modulation | 16K ∅ F3E(Wide) 8K ∅ F3E(Narrow) |
| Rated Audio Distortion | 0.05 |
| Adjacent Power | ≥65 dB(Wide)/60 dB(Narrow) |
| Modulation Limitation | ≤5KHz(Wide)/2.5KHz(Narrow) |
| Receiver | |
| Sensitivity | ≤-123dB (12dB SINAD) |
| Adjacent Selectivity | ≥60dB(Wide)/ 55dB (Narrow) |
| Intermodulation Rejection Ratio | ≥60dB(Wide)/ 55dB (Narrow) |
| Spurious Suppression | ≥60dB(Wide)/ 55dB (Narrow) |
| Rated Audio Output Power | 0.5W |
| Rated Audio Distortion | ≤5% |

Accessories

• Standard Accessories



• Optional Accessories



Fujian Belfone Communications Technology Co., Ltd.
Add: A15,Huaqiao Economic Development Zone, Shuangyang,
Luojiang, Quanzhou,Fujian,China 36200
Tel: +86 595 28396717
Fax: +86 595 22771635
Email: overseas@belfone.com
Website: www.belfone.com



To order in your local place, please contact:

BF-7110

Analog Portable

Belfone long talk range analog radio BF-7110 comes with a tensile antenna to further extend the communication coverage. And the adjustable output power delivers more flexibility. Its robust body and rich features both serve to make it an ideal choice for security workers, construction sites and many more fields of work.

Main Features

- Switchable Power
- Time-out Timer (TOT)
- QT/DQT
- BCL
- Squelch Levels (0-9)
- Channel Prompt
- Low Battery Alert
- VOX



www.belfone.com

