



NOTES:

1. RESISTANCE VALUES ARE SHOWN IN OHMS UNLESS OTHERWISE NOTED. (K-KILO OHM, M-MEG OHM)
2. RESISTOR WATTAGES ARE (1/10W) UNLESS OTHERWISE NOTED
3. CAPACITANCE VALUES ARE INDICATED IN MICRO FARADS UNLESS OTHERWISE NOTED. (P-PICO-MICRO FARAD)
4. ALL CAPACITORS TEMPERATURE CHARACTERISTICS ARE (C) (LESS THAN 100PPM) OR (D) (MORE THAN 100PPM) UNLESS OTHERWISE NOTED.
5. CHIP PARTS ARE NOT SPECIFIED IN THIS DRAWING PLEASE REFER TO THE PARTS LIST FOR THE CHIP PARTS.

REVISIONS:

REV. CODE	DATE	LOYS/RNB	REVISIONS

DESIGNED BY M. H. WALKER	DRAWN BY MOKA	UNIDEN No. UT373ZH	MODEL No. WALKER
CHECKED BY M. H. WALKER	APPROVED BY AUG/80/2005	TITLE SCHEMATIC DIAGRAM	DRAWING No. E12-7775
REV. No.			UNIDEN CORP.